

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 1.1$ (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **34 mm**

Maximum acoustic insulation: **R_w = 40 dB**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 3

Water tightness (EN 12208):

Class 7A

Wind resistance (EN 12210):

Class C5

Security Test: **PAS24**

Passed

*Reference test 1.80 x 2.20 m / 2 sashes

SECTIONS	Frame 120 mm and 115 mm Three-rail 185 mm Sash 50 mm
PROFILE THICKNESS	Balcony 1.5 mm
MAXIMUM DIMENSIONS	Width (L) = 2.500 mm Height (H) = 3.000 mm
MAXIMUM WEIGHT/SASH	280 Kg

Please consult maximum dimensions according to types.

EXTRUSION ALLOY	6063 T-5
POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass : 20 y 25 mm
OPENING POSIBILITIES	Sliding 1 rail (sash + fixed light) 2 and 3 rails Galandage

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

